



Albany, Oregon

Such sidewalks to have a slope of one fourth of an inch to the curb from the inside of the curb to the outer edge of sidewalk, and at the curb on the same shall be rounded to conform to the quadrant of a circle with a thirty inch radius and at the outer corners at the sidewalk is rounded to conform to the quadrant of a circle with a forty-four inch radius.

Materials used in the construction of sidewalks shall be of the best quality of Portland Cement and that the top surface of all concrete work shall be set in a material, shall be kept wet, or at least covered by covering with canvas, awning or other moisture retaining material.

That all materials used in the construction of sidewalks and curbs, as well as the construction itself, shall be promptly inspected by a city engineer or Superintendent of Streets.

Passed the Council June 10th, 1914  
Approved June 11th, 1914

Attest:

F. E. Van Tassel  
Recorder of the City of Albany

L. M. Gurl  
Mayor

CITY RECORDER'S CERTIFICATE

State of Oregon, }  
County of Linn } ss.

I, F. E. Van Tassel, Recorder of the City of Albany, Linn County, and State of Oregon, do hereby certify that the foregoing annexed copy of

Ordinance No. 7225

has been by me carefully compared with the original Ordinance Bill No. 801

now on file in my office, and that it is a true and correct copy of all and the whole of said Ordinance

Bill No. 801, as passed by the Council of the City of Albany, Oregon, June 10th, 1914

Witness, my hand and official signature and the seal of the City of Albany, this 12th day of June, 1914

F. E. Van Tassel

Recorder of the City of Albany