



SECTION A-A

GENERAL NOTES

1. CONTACT THE UNITED STATES POSTAL SERVICE FOR LOCATION OF CLUSTER MAILBOX UNITS (CBUs). LOCATION SUBJECT TO APPROVAL BY THE CITY.
2. CBUs SHALL BE PROVIDED WITH AN UNOBSTRUCTED ACCESS PAD MEASURING NOT LESS THAN SIX FEET WIDE BY SIX FEET LONG, CENTERED ON THE FACE OF THE CBU.
3. WHERE LOCATED WITHIN A PLANTER STRIP THE ACCESS PAD SHALL BE CONTINUOUS FROM THE BACK OF CURB TO EDGE OF SIDEWALK, SEPARATED BY COLD JOINTS.
4. THE ACCESS PAD SHALL BE CONSTRUCTED OF PORTLAND CEMENT CONCRETE AND SHALL HAVE A SLOPE OF 1.5% IN ANY DIRECTION (2.0% MAX.) AND SHALL BE FLUSH WITH ADJACENT SIDEWALK AND TOP OF CURB.
5. ADJACENT SIDEWALKS MAY BE USED IN MEASURING THE AREA OF THE ACCESS PAD.
6. CBUs SHALL BE LOCATED NO MORE THAN FIFTY FEET FROM A CURB RAMP, AS MEASURED FROM THE CENTER OF THE CURB RAMP TO THE CENTER FACE OF THE FURTHEST CBU.
7. CBUs SHALL BE CONNECTED BY A CONTINUOUS ACCESSIBLE WAY (SIDEWALK) TO THE CURB RAMP.
8. CBUs SHALL BE INSTALLED ON STREETS WITH A MAXIMUM GRADE OF 4% UNLESS APPROVED BY THE CITY ENGINEER.

CITY OF ALBANY, OREGON PUBLIC WORKS DEPARTMENT	
CLUSTER MAILBOX UNITS (CBUs)	
NO SCALE	JUNE 2023
NO. 202B	